


Cambridge™ nylon adjustable ties are great for securing heavy duct take-offs and large cable bundles. Manufactured for durability, easy to install and offer up to 175 lb. tensile strength.



CAMBRIDGE™ CABLE & DUCT TIES



A TRUSTED NAME IN HVAC

- All Cambridge™ cable ties feature a bent tip design for a smooth insertion in hard-to-reach places.
- Rounded tips prevent users from cutting themselves on sharp edges.
- UV black cable and duct ties are specially manufactured to resist the sun's harmful UV rays.
- Minimum Installation Temperature: 5°F (-15°C)
- 175 lb. Duct Ties have been investigated to ANSI/UL 181B
 - UL 2043: "Fire Test for Heat and Visible Smoke Release for Discrete Products and Their Accessories Installed in Air-Handling Spaces."
 - These products have been found to be suitable for use in plenums in accordance with the "International Mechanical Code," "Uniform Mechanical Code," and ANSI/NFPA 90A, "Installation of Air-Conditioning and Ventilating Systems".

Part Number	Max. Tensile Strength	Length	Color	Case Qty
(100 PACK) CABLE TIES				
CT6-40C0W	40 lb.	6"	UV Black	250
CT8-50C0W	50 lb.	8"	UV Black	100
CT8-50C9	50 lb.	8"	Natural	100
CT11-50C0W	50 lb.	11"	UV Black	50
CT11-50C9	50 lb.	11"	Natural	50
CT14-50C0W	50 lb.	14.5"	UV Black	50
CT17-50C9	50 lb.	17"	Natural	50
(50 PACK) DUCT TIES				
CT24-175K0W	175 lb.	24.5"	UV Black	10
CT24-175K9	175 lb.	24.5"	Natural	10
CT36-175K0W-B	175 lb.	36"	UV Black	10
CT36-175K9-B	175 lb.	36"	Natural	10
CT48-175K0W-B	175 lb.	48"	UV Black	10
CT48-175K9-B	175 lb.	48"	Natural	10

Call to request additional sizes

Cable & Duct Ties UL Listed for Safety



FILE NO. E257228
Covers All Cable & Duct Ties



181B-C
FILE NO. MH29023
Covers 175lb. Duct Ties

#Trust the (G)